

Trauma Sensors

Featuring Masimo SET® Measure-through Motion and Low Perfusion™ Pulse Oximetry



Trauma Sensors automatically configure Masimo SET® and rainbow SET™ devices for the fastest averaging time and maximum sensitivity settings



Trauma Sensor Options



- > VelAid™ SofTouch design allows for quick, easy sensor application and repositioning
- > Hook and loop attachment strip keeps the sensor secure, even when site is wet



RD SET™ TRAUMA



LNCS® TRAUMA



M-LNCS™ TRAUMA

Specifications

ACCURACY (ARMS)¹

Oxygen Saturation (SpO ₂ %) Accuracy Range	70%–100%
No Motion Adults	2%
Motion Adults	3%
Low Perfusion Adults	2%
Pulse Rate (bpm) Accuracy Range	25–240 bpm
No Motion Adults	3 bpm
Motion Adults	5 bpm
Low Perfusion Adults	3 bpm

INFORMATION

Single-patient-use / Non-sterile / Packaged 20 per box / Does not contain natural rubber latex

WEIGHT RANGE

RD SET Trauma	>30 kg, finger application
LNCS Trauma	>30 kg, finger application
M-LNCS Trauma	>30 kg, finger application

ORDERING INFORMATION

RD SET Trauma	4011
LNCS Trauma	2411
M-LNCS Trauma	2521

¹ ARMS Accuracy is a statistical calculation of the difference between device measurements and reference measurements. Approximately two-thirds of the device measurements fell within \pm ARMS of the reference measurements in a controlled study.

Caution: Federal (USA) law restricts this device to sale by or on the order of a physician. See instructions for use for full prescribing information, including indications, contraindications, warnings, and precautions.

Masimo U.S.
Tel: 1 877 4 Masimo
info-america@masimo.com

Masimo International
Tel: +41 32 720 1111
info-international@masimo.com

